

CGC

IC-CUSHION **LPG**
13,500 / 15,500 lbs.
(6000 / 7000 kg)



STANDARD SPECIFICATIONS

60/70

Manufacturer's Designation		CGC 60	CGC 70
Load Capacity / Rated Load	lbs(kg)	13,500 (6000)	15,500 (7000)
Height Overhead Guard	in(mm)	91.0 (2306)	91.0 (2306)
Width	in(mm)	58.8 (1494)	58.8 (494)
Right Angle Stack (add load length and clearance)	in(mm)	124.0 (3149)	126.3 (3208)
Outside Turning Radius	in(mm)	105.1 (2669)	107.4 (2728)
Travel speed loaded / unloaded	mph (kph)	10.3 (16.5) / 10.4 (16.5)	10.2 (16.3) / 10.4 (16.6)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	GM / Vortec 4300LT / 93(69) @ 2400	GM / Vortec 4300LT / 93(69) @ 2400

STANDARD FEATURES

Two-speed transmission • Full range of Standard and Triple Stage lift heights and options available • Isolated operator cell • Full access clamshell hood • GM 4.3 liter V6 LPG • CLARK monitor engine shutdown protection • High visibility uprights • Two-pedal inch-brake system • Overhead tilt cylinders • Clark safety seat



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.